

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	250/80 R 18
LI/SS	125 A8/125 B

Dimensions US Standard

Usa code	94066131
Section Width (inch)	9.8
Overall Diameter (inch)	32.9
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	100
Rim Rec	W 8
Rim Alt	W 7 ; W 9
ECE	E11-106R-006605
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	57	52	58
30	1280	1500	1720	1930	2150	2340	2590	2730	2990	3240	3460	3640
25	1280	1500	1720	1930	2150	2340	2590	2730	2990	3240	2460	3640
20	1370	1610	1840	2070	2300	2500	2780	2930	3210	3480	3710	3900
5 LT	1720	2010	2300	2590	2890	3130	3470	3670	4010	4350	4640	4880
5 HT	1370	1610	1840	2070	2300	2500	2780	2930	3210	3480	3710	3900

Printed on 4/26/2024 8:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..