

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	250/85 R 28 (9.5 R 28)
LI/SS	112 A8/B

Dimensions International Standard

Section Width (mm)	251
Overall Diameter (mm)	1137
Static Loaded Radius (mm)	519
Rolling Circumference (mm)	3421
SRI (mm)	550
Rim Rec	W 8
Rim Alt	W 7 ; W 9
ECE	E4-106R-000646
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	620	720	820	920	1020	1120
40	620	720	820	920	1020	1120
30	660	770	880	985	1095	1200
10 LT	830	965	1100	1235	1370	1505
10 HT	660	770	880	985	1095	1200

Printed on 4/26/2024 8:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..