

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 28 (12.4 R 28)
LI/SS	124 A8/B

Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1255
Static Loaded Radius (mm)	569
Rolling Circumference (mm)	3743
SRI (mm)	600
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000615
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	880	1025	1170	1315	1460	1600
40	880	1025	1170	1315	1460	1600
30	945	1100	1255	1410	1565	1715
10 LT	1180	1375	1570	1760	1955	2145
10 HT	945	1100	1255	1410	1565	1715

Printed on 5/5/2024 2:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..