

# AGRIMAX RT 855 - Technical Specifications



## Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 28 (13.6 R 28)
LI/SS	139 A8/B

Dimensions US Standard

Usa code	94073269
Section Width (inch)	13.9
Overall Diameter (inch)	51.8
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	156
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-008233
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	47
30	2090	2470	2840	3160	3540	3860	4230	4560	4980	5360
25	2090	2470	2840	3160	3540	3860	4230	4560	4980	5360
20	2250	2650	3050	3390	3790	4140	4540	4880	5350	5740
5 LT	2810	3310	3810	4240	4750	5180	5690	6120	6690	7190
5 HT	2250	2650	3050	3390	3790	4140	4540	4880	5350	5740

Printed on 5/5/2024 4:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..