

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	420/85 R 34 (16.9 R 34)
LI/SS	142 A8/B

Dimensions International Standard

Section Width (mm)	438
Overall Diameter (mm)	1578
Static Loaded Radius (mm)	709
Rolling Circumference (mm)	4702
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-000656
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1460	1700	1935	2175	2415	2650
40	1460	1700	1935	2175	2415	2650
30	1565	1820	2075	2330	2585	2840
10 LT	1960	2280	2600	2920	3240	3555
10 HT	1565	1820	2075	2330	2585	2840

Printed on 5/5/2024 11:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..