

# AGRIMAX RT 855 - Technical Specifications



## Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	157 A8/B

## Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1951
Static Loaded Radius (mm)	858
Rolling Circumference (mm)	5782
SRI (mm)	925
Rim Rec	DW 16 L ; W 16 A ; DD 16
Rim Alt	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
ECE	E4-106R-000792
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	2270	2640	3015	3385	3755	4125
40	2270	2640	3015	3385	3755	4125
30	2430	2830	3225	3625	4020	4415
10 LT	3045	3540	4040	4535	5035	5530
10 HT	2430	2830	3225	3625	4020	4415

Printed on 4/26/2024 11:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..