

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	320/90 R 50 (12.4 R 50)
LI/SS	150 A8/B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	1846
Static Loaded Radius (mm)	873
Rolling Circumference (mm)	5618
SRI (mm)	875
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E4-106R-000787
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	1410	1845	2245	2450	2615	2850	3085	3350	-
40	1410	1845	2245	2450	2615	2850	3085	3350	-
30	1510	1975	2405	2620	2800	3050	3300	3585	-
10	1960	2565	3120	3420	3620	3970	4325	4675	5025

Printed on 4/26/2024 3:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..