

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	420/90 R 30
LI/SS	147 A8/B

Dimensions International Standard

Section Width (mm)	418
Overall Diameter (mm)	1518
Static Loaded Radius (mm)	684
Rolling Circumference (mm)	4571
SRI (mm)	700
Rim Rec	DW13
Rim Alt	W 14 L
ECE	E11-106R-006021
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4
50	1665	2155	2645	2895	3075
40	1665	2155	2645	2895	3075
30	1780	2310	2835	3100	3295
10	2495	3235	3970	4340	4615

Printed on 4/17/2024 9:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..