

## AGRIMAX RT 945 - Technical Specifications



### Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	420/90 R 30
LI/SS	147 A8/B

## Dimensions US Standard

Usa code	94063857
Section Width (inch)	16.5
Overall Diameter (inch)	59.8
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	180
Rim Rec	DW13
Rim Alt	W 14 L
ECE	E11-106R-006021
TRA Code	R1W

## Load capacity (lbs)

mph / psi	12	17	23	29	35
30	3670	4750	5830	6380	6780
25	3670	4750	5830	6380	6780
20	3920	5090	6250	6830	7260
5	5500	7130	8750	9570	10170

Printed on 4/20/2024 6:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..