

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/90 R 24 (8.3 R 24)
LI/SS	107 A8/B

Dimensions International Standard

Section Width (mm)	214
Overall Diameter (mm)	1010
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3027
SRI (mm)	475
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001818
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
50	460	530	605	685	765	840	910	975	-
40	460	530	605	685	765	840	910	975	-
30	495	565	650	735	820	900	975	1045	-
10	675	780	865	955	1055	1160	1350	1425	1465

Printed on 4/26/2024 10:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..