

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	270/95 R 32 (11.2 R 32)
LI/SS	136 A8/B

Dimensions US Standard

Usa code	94021857
Section Width (inch)	10.8
Overall Diameter (inch)	52.2
Static Loaded Radius (inch)	24.2
Rolling Circumference (inch)	160.5
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000776
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
25	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
20	2070	2700	3280	3600	3810	4190	4550	4930	5290	-
5	2300	2900	3560	4230	4890	5040	5630	6230	6820	7410

Printed on 4/26/2024 7:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..