

# AGRIMAX RT 955 - Technical Specifications



## Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	270/95 R 36 (11.2 R 36)
LI/SS	139 A8/B

## Dimensions US Standard

Usa code	94027484
Section Width (inch)	10.8
Overall Diameter (inch)	56.2
Static Loaded Radius (inch)	26.2
Rolling Circumference (inch)	170.7
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000659
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2090	2730	3330	3650	3860	4230	4610	4980	5350	-
25	2090	2730	3330	3650	3860	4230	4610	4980	5350	-
20	2250	2930	3570	3910	4140	4540	4950	5350	5740	-
5	2490	3140	3860	4590	5310	5470	6120	6760	7400	8040

Printed on 4/26/2024 6:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..