

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	300/95 R 46 (12.4 R 46)
LI/SS	148 A8/B

Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	1738
Static Loaded Radius (mm)	812
Rolling Circumference (mm)	5318
SRI (mm)	825
Rim Rec	W 9
Rim Alt	W 10 ; W 11 ; DW 10 ; DW 11
ECE	E4-106R-000790
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1105	1295	1485	1670	1860	2020	2205	2365	2585	2805	2995	3150	-
40	1105	1295	1485	1670	1860	2020	2205	2365	2585	2805	2995	3150	-
30	1185	1385	1590	1790	1995	2160	2365	2535	2770	3005	3210	3375	-
20	1360	1590	1825	2055	2290	2480	2715	2910	3180	3450	3685	3875	-
10	1525	1785	2045	2310	2570	2785	3045	3265	3570	3875	4135	4350	4725

Printed on 5/5/2024 9:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..