

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 380/105 R 50
LI/SS	179 D

Dimensions US Standard

Usa code	94048113
Section Width (inch)	15.7
Overall Diameter (inch)	80.7
Static Loaded Radius (inch)	36.8
Rolling Circumference (inch)	244.5
Rim Rec	W 13 A
Rim Alt	W 12 ; DW 12 ; DW 13 ; DW 13 L
ECE	E4-106R-002397
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	7460	8390	9160	9640	10100	10410	10720	11350	11810	12270	12750	13210	13520	13990	14300	14920	15550
From 40 to 25	8210	9230	10080	10600	11100	11450	11790	12470	12990	13500	14010	14520	14860	15380	15720	16410	17090
20	8360	9410	10280	10810	11330	11680	12020	12720	13240	13760	14290	14810	15160	15680	16030	16730	17430
12	8530	9590	10490	11020	11550	11910	12260	12970	13510	14040	14570	15110	15460	15990	16350	17060	17770
5	9020	10150	11080	11660	12220	12590	12970	13720	14280	14840	15410	15980	16350	16910	17290	18040	18800

Printed on 5/4/2024 3:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..