

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	IF 710/75 R 32 CFO
LI/SS	183 A8/B

Dimensions US Standard

Usa code	94059249
Section Width (inch)	28.2
Overall Diameter (inch)	74
Static Loaded Radius (inch)	33.5
Rolling Circumference (inch)	222.6
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-005025

Load capacity (lbs)

mph / psi	9	12	15	20	23	29	35	41	46
30	7530	8870	10230	12730	13890	15240	16400	17940	19300
25	7530	8870	10230	12730	13890	15240	16400	17940	19300
20	8060	9500	10950	13630	14870	16310	17560	19200	20650
10 Cyc*	11670	13760	15850	19740	21540	23630	25430	27820	29900
5 Cyc*	13550	15970	18410	22920	25000	27440	29520	32300	34720

* - * For 15 & 10 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 4/19/2024 4:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..