

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/70 R 24
LI/SS	130 A8 / 130 B

Dimensions US Standard

Usa code	94069460
Section Width (inch)	16.5
Overall Diameter (inch)	49.1
Static Loaded Radius (inch)	21.9
Rolling Circumference (inch)	146.8
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-007206

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2310	2690	3070	3440	3820	4190
25	2310	2690	3070	3440	3820	4190
20	2470	2880	3290	3690	4090	4490
5 LT	3100	3610	4120	4620	5130	5630
5 HT	2470	2880	3290	3690	4090	4490

Printed on 4/26/2024 9:36 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..