

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/65 R 28 NRO
LI/SS	163 D

Dimensions International Standard

Section Width (mm)	597
Overall Diameter (mm)	1491
Static Loaded Radius (mm)	655
Rolling Circumference (mm)	4453
SRI (mm)	700
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 L
ECE	E11-106R-007602
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.8	2.0
70	2265	2620	2975	3375	3690	4000	4440
From 65 to 40	2490	2880	3270	3705	4050	4390	4875
30	2540	2940	3335	3785	4130	4480	4975
20	2590	2995	3400	3855	4210	4565	5070
10	2740	3170	3595	4080	4455	4830	5365
*Upto 10 Cyc with front loader	3485	4030	4575	5190	5665	6145	6825
10 HT	2540	2940	3335	3785	4130	4480	4975

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 12/2/2023 11:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..