

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 750/70 R 44
LI/SS	186 D

Dimensions International Standard

Section Width (mm)	760
Overall Diameter (mm)	2175
Static Loaded Radius (mm)	958
Rolling Circumference (mm)	6450
SRI (mm)	1025
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-006765
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	4065	4670	5360	6055	6745	7435	8130	8645
From 65 to 40	4465	5130	5890	6650	7410	8170	8930	9500
30	4555	5235	6010	6785	7560	8335	9110	9690
20	4645	5340	6130	6920	7710	8500	9290	9880
10	4915	5645	6480	7315	8155	8990	9825	10450
*Upto 10 Cyc with front loader	6255	7185	8250	9310	10375	11440	12505	13300
10 HT	4555	5235	6010	6785	7560	8335	9110	9690

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 4/25/2024 10:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..