

AGRIMAXFACTOR - Technical Specifications



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	520/70 R 38
LI/SS	150 D/153 A8

Dimensions US Standard

Usa code	94070725
Section Width (inch)	20.3
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	31.3
Rolling Circumference (inch)	206.3
Rim Rec	W 16 L
Rim Alt	W 15 L ; W 18 L
ECE	E11-106R-007609
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	4070	4730	5400	6060	6720	7390
30	4280	4970	5670	6370	7070	7760
25	4450	5180	5910	6640	7360	8090
20	4680	5450	6210	6980	7740	8500
5 LT	5450	6340	7230	8120	9020	9900
5 HT	4680	5450	6210	6980	7740	8500

Printed on 4/14/2024 5:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..