

# AIROMAX AM 27 - Technical Specifications



## Description

AIROMAX AM 27 is the ideal road-oriented tire for construction applications with cranes. It features extraordinary heat resistance and outstanding riding comfort. AIROMAX AM 27 is a high-speed tire particularly suitable for all operations requiring a high level of handling.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Industrial: Mobile Crane

|           |                             |
|-----------|-----------------------------|
| Version   | STANDARD                    |
| Type      | TT                          |
| Tyre Size | 385/95 R 24<br>(14.00 R 24) |
| LI/SS     | 170 F                       |

# Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Overall Width (mm)         | 372             |
| Overall Diameter (mm)      | 1363            |
| Static Loaded Radius (mm)  | 626             |
| Rolling Circumference (mm) | 4175            |
| Rim Rec                    | 10.00W          |
| ECE                        | E11-54R-0015910 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 9.00 |
| 80         | 6000 |

Printed on 4/27/2024 5:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..