

AIROMAX AM 27 - Technical Specifications



Description

AIROMAX AM 27 is the ideal road-oriented tire for construction applications with cranes. It features extraordinary heat resistance and outstanding riding comfort. AIROMAX AM 27 is a high-speed tire particularly suitable for all operations requiring a high level of handling.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Mobile Crane

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 F

Dimensions US Standard

Usa code	94044214
Overall Width (inch)	14.6
Overall Diameter (inch)	53.7
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	164.4
Rim Rec	10.00/1.5
ECE	E11-54R-0015911

Load capacity (lbs)

mph / psi	130
50	13200

Printed on 4/11/2024 4:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..