

AS 505 - Technical Specifications



Description

AS 505 is best suited for soil tillage operations with trailers and implement machinery. It features excellent self-cleaning properties and increased traction on the ground, especially on muddy soil. The tire also ensures a long tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

| | |
|--------------------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 6.5/80 - 15 |
| LI/SS DRIVE WHEEL | 92 A8 |
| LI/SS FREE ROLLING | 104 A8 |

Dimensions International Standard

| | |
|----------------------------|------------------|
| Ply Rating | 8 |
| Section Width (mm) | 171 |
| Overall Diameter (mm) | 695 |
| Static Loaded Radius (mm) | 325 |
| Rolling Circumference (mm) | 2106 |
| Rim Rec | 5.0 |
| Rim Alt | 4½ K ; 5 K ; 5 J |
| ECE | E4-106R-002660 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 4.80 |
| 10 FR | 1260 |
| 25 FR | 1070 |
| 30 FR | 1010 |
| 40 FR | 900 |
| 10 DW | 880 |
| 25 DW | 750 |
| 30 DW | 705 |
| 40 DW | 630 |

Printed on 4/29/2024 9:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..