



AS 509 - Data Sheet

Description

AS 509 has been specially designed for trailers, balers and implement machinery. It ensures high load capacity at low inflation pressure protecting crops. AS 509 provides great traction and self-cleaning properties.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer



| SIZE | Version | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|----------|-------------------|--------------------|----|----------|---------|-----|------|-----|------|------|-----------------|
| 550/45 - 22.5 | STANDARD | 141 A8/137 B | 153 A8/149 B | 12 | AG 16.00 | | 540 | 1065 | 479 | 3250 | TL | E11-106R-006445 |
| 550/45 - 22.5 | STANDARD | 154 A8/150 B | 166 A8/162 B | 20 | AG 16.00 | | 540 | 1065 | 479 | 3250 | TL | E11-106R-004545 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/5/2024 8:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..