

## AT 110 - Data Sheet



### Description

AT 110 is BKT's tire suitable for all-terrain applications with ATVs. Thanks to its extraordinary steering control, AT 110 is the ideal front axle tire for your vehicle.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: ATV

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 20 X 7 - 8	STANDARD	94000821	4	5.5 AT	6.0 AT	7.2	20	TL	
AT 21 X 8 - 9	STANDARD	94000791	4	6.5 AT	6.0 AT	8	21.3	TL	
AT 21 X 7 - 10	STANDARD	94026821	4	5.5 AT	6.0 AT	7	20.9	TL	
AT 22 X 8 - 10	STANDARD	94000807	4	6.5 AT	6.0 AT	8	21.6	TL	
AT 23 X 7 - 10	STANDARD	94026838	4	5.5 AT	6.0 AT	7	23	TL	E4-75R-0006334

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 8:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..