

## AT 171 - Technical Specifications



### Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: ATV • Mud Bogger Tractor

Version	STANDARD
Type	TT
Tyre Size	AT 38 X 10 - 20
LI/SS	93 A8 / 69 F

## Dimensions International Standard

<b>Ply Rating</b>	6
<b>Section Width (mm)</b>	235
<b>Overall Diameter (mm)</b>	950
<b>Static Loaded Radius (mm)</b>	442
<b>Rolling Circumference (mm)</b>	2835
<b>Rim Rec</b>	W 8
<b>Rim Alt</b>	W 7
<b>TRA Code</b>	R1W+

## Load capacity (Kg)

	km/h / bar	1.40	1.00
<b>40 MUD BOGGING</b>		650	-
<b>80 MUD BOGGING</b>		325	-
<b>40 CASUAL TRANSPORT</b>		-	530
<b>80 CASUAL TRANSPORT</b>		-	265

Printed on 4/18/2024 8:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..