

AW 705 - Technical Specifications



Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TT
Tyre Size	14.0/65 - 16
LI/SS FREE ROLLING	134 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	353
Overall Diameter (mm)	870
Static Loaded Radius (mm)	388
Rolling Circumference (mm)	2549
Rim Rec	11.0

Load capacity (Kg)

km/h / bar	2.80
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120

Printed on 4/24/2024 6:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..