

AW 705 - Technical Specifications



Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	15.0/70 - 18
LI/SS FREE ROLLING	151 A8

Dimensions US Standard

Usa code	94025749
Ply Rating	16
Section Width (inch)	15.9
Overall Diameter (inch)	39.8
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	121.7
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-002266

Load capacity (lbs)

	mph / psi	62
	5 FR	10650
	15 FR	9050
	20 FR	8520
	25 FR	7610

Printed on 5/6/2024 1:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..