

AW 708 - Technical Specifications

Description

AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer
Industrial: Trailer



Version	STANDARD
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	144 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	470
Overall Diameter (mm)	866
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2536
Rim Rec	16.00
ECE	E4-106R-001883

Load capacity (Kg)

	km/h / bar	2.80
	10 FR	3920
	25 FR	3330
	30 FR	3135
	40 FR	2800

Printed on 4/20/2024 7:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..