

## AW 708 - Technical Specifications

### Description

AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Implement Machinery • Trailer  
Industrial: Trailer



Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	136 A8

Dimensions US Standard

Usa code	94010271
Ply Rating	10
Section Width (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00
ECE	E11-106R-003514

Load capacity (lbs)

mph / psi	36
5 FR	6910
15 FR	5870
20 FR	5530
25 FR	4940

Printed on 5/2/2024 12:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..