

AW 711 - Technical Specifications



Description

AW 711 is a radial implement tire specially designed for modern farming, and suitable for haulage, hay harvesting and soil tillage applications. Thanks to its special tread compound, AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption. Thanks to the VF technology, AW 711 can carry heavy loads at low inflating pressure.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Hay Harvester • Implement Machinery

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	15 R 19.5
LI/SS	139 D

Dimensions International Standard

Section Width (mm)	389
Overall Diameter (mm)	1019
Static Loaded Radius (mm)	471
Rolling Circumference (mm)	3094
SRI (mm)	475
Rim Rec	11.75
Rim Alt	12.75
ECE	E11-106R-006649

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	5.5
65	660	855	1045	1170	1365	1535	1705	1850	2045	2285	2430
50	840	1090	1340	1495	1745	1960	2180	2365	2615	2925	3110
40	885	1145	1405	1565	1830	2055	2285	2480	2740	3065	3260
25	960	1245	1530	1710	1995	2240	2490	2705	2990	3345	3555
10	1335	1730	2125	2370	2765	3110	3455	3755	4150	4640	4935

Printed on 4/28/2024 9:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..