

AW 711 - Technical Specifications



Description

AW 711 is a radial implement tire specially designed for modern farming, and suitable for haulage, hay harvesting and soil tillage applications. Thanks to its special tread compound, AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption. Thanks to the VF technology, AW 711 can carry heavy loads at low inflating pressure.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Hay Harvester • Implement Machinery

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	395/55 R 16.5
LI/SS	152 A8/B

Dimensions US Standard

Usa code	94053469
Section Width (inch)	15.5
Overall Diameter (inch)	33
Static Loaded Radius (inch)	14.4
Rolling Circumference (inch)	99.1
Rim Rec	12
ECE	E11-106R-002997

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
30	2350	3050	3760	4310	5020	5720	6110	6730	7360	7830
25	2350	3050	3760	4310	5020	5720	6110	6730	7360	7830
20	2630	3430	4220	4830	5620	6420	6840	7550	8260	8770
15	2800	3640	4480	5130	5960	6800	7270	8010	8760	9310
10	2970	3860	4740	5430	6320	7210	7700	8490	9280	9870
5	3300	4280	5270	6030	7020	8000	8550	9420	10310	10960

Printed on 12/10/2023 10:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..