

## AW 711 - Technical Specifications



### Description

AW 711 is a radial implement tire specially designed for modern farming, and suitable for haulage, hay harvesting and soil tillage applications. Thanks to its special tread compound, AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption. Thanks to the VF technology, AW 711 can carry heavy loads at low inflating pressure.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Hay Harvester • Implement Machinery

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 340/65 R 18
LI/SS	153 A8/B

## Dimensions International Standard

Section Width (mm)	330
Overall Diameter (mm)	899
Static Loaded Radius (mm)	381
Rolling Circumference (mm)	2703
SRI (mm)	450
Rim Rec	W 11
ECE	E11-106R-002992

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
From 10 to 50 km/h	1170	1535	1865	2155	2485	2815	3030	3325	3650

Printed on 11/30/2023 5:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..