



AW 729 - Data Sheet

Description

AW 729 is an agricultural tire specifically designed for transport, hay harvesting, baling and soil tillage applications. Its rounded shoulder and three central grooves tread design provide low soil compaction and avoids damages to the field.

AW 729 is the ideal tire for modern farming, and it is suited for both on-and-off-the-road usage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer



SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
340/55 - 16 (13.0/55 - 16)	STANDARD	121 A8	133 A8		11.0		343	785	358	2358	TL	E11-106R-006421
15.0/55 - 17	STANDARD	122 A8	134 A8	10	13.00	13; W 13	385	850	377	2560	TL	E11-106R-006434
380/55 - 17	STANDARD	122 A8	134 A8	10	13.00	13; W 13	385	850	377	2560	TL	E11-106R-008727
480/45 - 17	STANDARD	134 A8	146 A8		16.00		480	866	400	2526	TL	E11-106R-006798
500/50 - 17	STANDARD	137 A8	149 A8		16.00		500	945	426	2885	TL	E11-106R-006616

Printed on 4/23/2024 11:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..