

AW 909 - Technical Specifications



Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS FREE ROLLING	126 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	274
Overall Diameter (mm)	760
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2227
Rim Rec	9.00
ECE	E4-106R-001541

Load capacity (Kg)

km/h / bar	4.70
10 FR	2380
25 FR	2025
30 FR	1905
40 FR	1700

Printed on 4/28/2024 9:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..