

## BK 826 - Technical Specifications



### Description

BK 826 has been specially designed for trailers in haulage applications. It is a bias tire featuring high load capacity thanks to its reinforced carcass. BK 826 is also available as "industrial" version that shows particular cut and chip resistance and is also suitable for backhoe loaders.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Industrial: Backhoe Loader • Trailer

Version	TRACTOR TRAILER
Type	TT
Tyre Size	8.25 - 16
LI/SS	134 A8

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	238
Overall Diameter (mm)	863
Rim Rec	6.50 H
Rim Alt	6.00 G

## Load capacity (Kg)

km/h / bar	7.60
40	2120

Printed on 5/3/2024 5:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..