

# COMMANDER (R) - Technical Specifications



## Description

COMMANDER (R) is an agricultural tire featuring a deep tread with strong lug bases for a longer tire life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tire for soil tillage, haulage and harvesting operations.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: Harvester • Tractor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 30
LI/SS	140 A8

## Dimensions US Standard

Usa code	94067640
Ply Rating	12
Section Width (inch)	17.3
Overall Diameter (inch)	58.3
Static Loaded Radius (inch)	27.1
Rolling Circumference (inch)	178.6
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-006618
TRA Code	R1

## Load capacity (lbs)

	mph / psi	36
	25	5510

Printed on 4/23/2024 6:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..