

# **EARTHMAX CRUSHER HAUL - Technical Specifications**



## **Description**

EARTHMAX CRUSHER HAUL is an All Steel radial tire designed for transport applications, both on and off the road, as well as mining operations. It features enhanced durability and mileage along with high load capacity thanks to the strong steel-belted construction and casing. The block-type tread pattern provides excellent traction. In addition, EARTHMAX CRUSHER HAUL ensures excellent riding comfort, less driving fatigue and superior handling.

#### UM

**US Standard** 

#### Construction



## Machinery

OTR: On/Off Truck

| Version   | STANDARD   |
|-----------|------------|
| Туре      | TT         |
| Tyre Size | 11.00 R 20 |
| LI/SS     | 152/149 J  |

## **Dimensions US Standard**

| Usa code                | 94070565 |
|-------------------------|----------|
| Ply Rating              | 18       |
| Overall Width (inch)    | 11.4     |
| Overall Diameter (inch) | 43.4     |
| Rim Rec                 | 8.00     |
| Rim Alt                 | 8.50     |

## Load capacity (lbs)

| mph / psi      | 120  |
|----------------|------|
| 62 Load Single | 7825 |
| 62 Load Dual   | 7165 |

#### Printed on 5/5/2024 7:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..