

EARTHMAX SR 30 - Technical Specifications



Description

EARTHMAX SR 30 (E-3/L-3) is an **All Steel** radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 193 A2 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94075256 |
| Overall Width (inch) | 20.8 |
| Overall Diameter (inch) | 58.5 |
| Static Loaded Radius (inch) | 26.1 |
| Rolling Circumference (inch) | 174.8 |
| Rim Rec | 17.00/2.0 |
| Rim Alt | 17.00/1.7 |
| Star Rating | ** |
| TRA Code | L3 |

Load capacity (lbs)

| | | | | | | |
|-----------|-------|-------|-------|-------|-------|-------|
| mph / psi | 76 | 80 | 83 | 87 | 91 | 94 |
| 5 | 21500 | 22000 | 22700 | 24000 | 24700 | 25400 |

Printed on 3/20/2024 10:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..