

EARTHMAX SR 30 - Technical Specifications



Description

EARTHMAX SR 30 (E-3/L-3) is an **All Steel** radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B

Dimensions International Standard

TKPH	230
Overall Width (mm)	689
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	766
Rolling Circumference (mm)	5200
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500

Printed on 4/24/2024 2:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..