

EARTHMAX SR 33 PLUS - Technical Specifications



Description

EARTHMAX SR 33 PLUS is a radial tire with a multi-block tread pattern specially designed for exceptional flotation and traction on soft, sandy and muddy surfaces. Its strong All Steel casing and belts provide excellent durability and resistance to snag and punctures. EARTHMAX SR 33 PLUS features excellent self-cleaning properties and provides superior stability.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	16.00 R 20
LI/SS	173/170 G

Dimensions International Standard

Overall Width (mm)	448
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	582
Rolling Circumference (mm)	3974
Rim Rec	11.25
Rim Alt	10.00W, 10.0
ECE	E11-54R-0017916

Load capacity (Kg)

km/h / bar	7.60
90	6500

Printed on 4/24/2024 9:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..