

# EARTHMAX SR 35 - Technical Specifications



## Description

Earthmax SR 35 is a low-profile All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It is ideal for operations requiring exceptional traction and flotation. Earthmax SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tire is available as cut-resistant compound for a maximum service life even under severe conditions.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	775/65 R 29
LI/SS	213 A2

## Dimensions International Standard

Overall Width (mm)	775
Overall Diameter (mm)	1752
Static Loaded Radius (mm)	787
Rolling Circumference (mm)	5311
Rim Rec	24.00/3.5
Rim Alt	24.00/3.0, 25.00/3.5
Star Rating	**
TRA Code	L3

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25
10	17500	18500	19000	19500	20000	20600

Printed on 4/23/2024 5:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..