

EARTHMAX SR 45 PLUS - Technical Specifications



Description

EARTHMAX SR 45 PLUS is an All Steel radial tire specially designed for rigid haul trucks. It is ideal for operations in long hauls. The tread pattern of the EARTHMAX SR 45 PLUS minimizes vibration and noise.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	STANDARD COMPOUND
Type	TL
Tyre Size	33.00 R 51
LI/SS	235 B

Dimensions International Standard

TKPH	705
Overall Width (mm)	910
Overall Diameter (mm)	3065
Static Loaded Radius (mm)	1369
Rolling Circumference (mm)	9313
Rim Rec	24.00/5.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	30000	30750	32500	33500	34500	35500	36500	37500	38750

Printed on 4/23/2024 12:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..