

EARTHMAX SR 452 - Technical Specifications



Description

EARTHMAX SR 452 is an All Steel radial tire specifically designed for Rigid Dump Trucks in transport operations. Its unique E-4 deep tread pattern stands for excellent traction and exceptional heat resistance, minimizing vibration and noise to provide best handling and comfort. Its strong steel casing and belts provide excellent stability and resistance to cuts and punctures. EARTHMAX SR 452 features a squared shoulder that maximizes ground contact for excellent maneuverability.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions US Standard

Usa code	94063383
TMPH	243
Overall Width (inch)	26
Overall Diameter (inch)	85.4
Static Loaded Radius (inch)	39.2
Rolling Circumference (inch)	264.9
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 9/26/2023 7:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..