



EARTHMAX SR 47 TP - Technical Specifications

Description

EARTHMAX SR 47 TP (E-4) is an All-Steel radial tire specially engineered for rigid haul trucks operating in conditions requiring maximum traction and puncture resistance. The E-4 tread depth ensure long wear even on long hauls, thus reducing downtime and increasing productivity. EARTHMAX SR 47 TP is perfect for any task demanding both traction and stability particularly on muddy or slippery terrain. Available in standard and cut-resistant compounds.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions US Standard

Usa code	94074211
TMPH	301
Overall Width (inch)	25.6
Overall Diameter (inch)	86
Static Loaded Radius (inch)	38.8
Rolling Circumference (inch)	260.8
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 5/8/2024 10:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..