

EARTHMAX SR 51 - Technical Specifications

Description

EARTHMAX SR 51 (L-5) is an **All Steel** radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Loader



| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 23.5 R 25 |
| LI/SS | 195 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 612 |
| Overall Diameter (mm) | 1660 |
| Static Loaded Radius (mm) | 743 |
| Rolling Circumference (mm) | 4882 |
| Rim Rec | 19.50/2.5 |
| Star Rating | * |
| TRA Code | L5 |

Load capacity (Kg)

| | | | | | |
|------------|-------|-------|-------|-------|-------|
| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
| 10 | 10300 | 10600 | 11200 | 11500 | 12150 |

Printed on 4/28/2024 9:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..