

## EM 933 SUPER - Data Sheet



### Description

EM 933 SUPER has been specially designed for excavators in digging and loading operations. Its exceptional sidewall design with a protruding kerb rib enables the close contact between two tires eliminating the need for a special rubber ring to prevent stone penetration. The unique tread design provides superior traction under heavy-duty service conditions. Additional features of EM 933 SUPER are outstanding riding comfort and enhanced self-cleaning properties.

### UM

US Standard

### Construction

✚ BIAS

### Machinery

Industrial: Excavator

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	Type
290/90 - 20	STANDARD	94070183	E2	152 B / 168 A2	18	8.00		11.6	41.5	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 7:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..