



EM 939 - Data Sheet



Description

EM 939 has been specially designed for excavators in road construction applications. It has a deeper tread and more lugs ensuring an extended tire life-cycle. The special lug design provides excellent traction during on/off road operations. The tire shows best lateral traction as well as outstanding self-cleaning features. The unique tread compound offers cut and chip resistance whereas the strong casing provides a long service life.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Excavator

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
10.00 - 20	STANDARD	18	7.5	7.0 ; 8.0	280	1075	TT
9.00 - 20	STANDARD	16	7.0	6.5 ; 7.5	260	1025	TT
9.00 - 20	STANDARD	18	7.0	6.5 ; 7.5	260	1025	TT

Printed on 4/23/2024 10:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..