

FARM 2000 - Technical Specifications



Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 8.3 - 24 |
| LI/SS | 105 A6 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 8 |
| Section Width (mm) | 211 |
| Overall Diameter (mm) | 995 |
| Static Loaded Radius (mm) | 473 |
| Rolling Circumference (mm) | 3032 |
| Rim Rec | W 7 |
| Rim Alt | W 6 |
| ECE | E11-106R-004094 |
| TRA Code | R1 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 3.10 |
| 30 | 925 |

Printed on 5/6/2024 1:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..