

## FL 252 - Technical Specifications



### Description

FL 252 is a tire suitable for hay harvesting applications with rotor rakes/tedders as well as for logistic operations using forklifts. This tire provides excellent durability while the specific tread pattern ensures maximum stability during lifting operations.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Rotor Rake / Tedder  
Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	7.00 - 12

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	192
<b>Overall Diameter (mm)</b>	683
<b>Rim Rec</b>	5.00 S

## Load capacity (Kg)

	km/h / bar	9.00
	25 LOAD WHEEL	2755
	25 STEER WHEEL	2120
	10 OTHER VEHICLES	2755
	25 OTHER VEHICLES	2120
	STATIC SIDE LOADER	3200

Printed on 4/25/2024 10:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..