

FL 630 SUPER - Technical Specifications



Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	159 D

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	518
Rolling Circumference (mm)	3533
SRI (mm)	550
Rim Rec	AG 20.00
ECE	E11-106R-005992

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1455	1635	2035	2315	2670	3030	3310	3630	3985
65	1600	1795	2235	2540	2935	3325	3635	3985	4375
50	1935	2175	2705	3075	3550	4025	4395	4820	5295
40	2175	2440	3035	3455	3990	4525	4940	5415	5950
25	2525	2840	3530	4015	4635	5260	5740	6295	6915
10	2875	3230	4020	4570	5280	5985	6540	7170	7875

Printed on 4/20/2024 3:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..